
TSS

35mm SOUND PROJECTOR





Tokiwa TSS

35mmSOUND PROJECTOR

TOKIWA TSS 35mm SOUD PROJECTOR

One complete set consists of:

- 2-TSS projection head-machines
- 2-Upper magazines & spools
- 2-Lower magazines & spools
- 2-Projection lenses
- 2-Cinemascope lens-holders
- 1-Film rewinder
- 2-TSS optical soundheads
- 2-TSS Pedestals
- 2-Lamphouses with mirrors & change over switch
- 2-Rectifiers

(TSS Sound System:)

- 1-Power amplifier
- 1-Exciter power supply
- 1-Cross over network
- 1-High frequency speaker system
- 1-Low frequency speaker system
- 1-Monitor speaker
- 1-Low frequency speaker cabinet
- TSS 35mm SOUND PROJECTOR is standard type for stationary use at theatres.
- TSS 35mm SOUND PROJECTOR is well designed with various merits after making improvement by long experience and is surely effective for perfect projection.

HEAD-MACHINE

- (1) The Head-machine of this TSS 35mm Sound Projector is fully covered and is dust-proofed by which it is always kept clean from the splash or leakage of oil. The lubricating oil in the bottom reservoir is automatically circulated as soon as the machine starts, through all the revolving parts of the head-machine by
- gear pump.


 (2) The transmission mechanism is made by wellselected steel after proper heat-treatment and precise works. Thus, together with the above automatic oil supply device, the long life and noiseless operation are guaranteed.
- (3) The aperture gate slides forward and backward horizontally by specially designed mechanism. By pulling the knob, the gate opens automatically and it is not necessary to move projection lens while threading the film.
- (4) The aperture-frame is water-cooled to protect the films from over-heating.
 - It has a separate aperture mask and a plate. The aperture mask can be inserted or fixed

easily and speedily. Framing can be made easily by framing lamp (pilot lamp.)

- The intermittent device, which is the most important part of the projector, is made with well-selected material, by our precise works and careful inspection.
- (6) The knob for framing device is well arranged to handle easily and for smooth movement.
- (7) The speed of connection shaft (to connect with the Soundhead) is 360 r.p.m. (The same r.p.m. as 16-T constant speed sprocket.)

SOUNDHEAD

- (1) By the rotary oil damped stabilizer of TSS Optical Soundhead, it prevents from minute tremor, it keeps the film speed constantly and also it avoids sound flutter entirely.
- (2) Drive motor is Induction-motor in vibrationproof type and is connected directly with the Soundhead Mechanism by the flexible coupl-
- (3) Exciter lamp holder is double system which enable the replacement of lamp speedily whenever it is broken.
- (4) Silicon photo diode is used instead of photo electric cell which guarantee the longer life and superior special features.



TSS PROJECTION HEAD-MACHINE

Type: Lubrication: Shutter: Cooling system: Framing: Magazine:

Reel:

Sprocket:

Fully enclosed Self-automatic Cylindrical shutter Water cooling

Intermittent framing 3,000 FT or 6,000 FT

Wire reel Upper-32 teeth Lower-32 teeth Intermittent-16 teeth

Net weight:

104 kgs.

= TSS-74K



Model

TSS-74K

TSS-X (XENON 2KW) TSS-X (XENON 3KW) TSS-X (XENON 4KW)

TSS-6000A-74K

TSS-6000A-2X


TSS-6000A-3X


TSS-6000A-4X


TSS-6000B-74K

TSS-6000B-2X TSS-6000B-3X

TSS-6000B-4X







TSS OPTICAL SOUNDHEAD

Type: Motor:

Rotary oil damped stabilizer 200W, Vibration proof type Induction motor, Direct coupled Double system 10V-5A Silicon photo diode Constant speed – 16 teeth Take-up – 16 teeth Rubber Less than 0.2% 94 kgs.

Exciter lamp holder: Photo detector: Sprocket:


Tension pad roller: Wow and flutter: Net weight:

94 kgs.

55		

						A STATE OF THE STA
Head-Machine	Soundhead	Pedestal	Lamphouse	Magazine	Rectifier	Sound System
TSS	TSS	TSS	TSS-74K (ARC CARBON)	3000FT.	TSS-85A	TSS
TSS	TSS	TSS	TX (2K XENON)	3000FT.	KRX-80	TSS
TSS	TSS	TSS	TXH (3K XENON)	3000FT.	KRX-100	TSS
TSS	TSS	TSS	TXH (4K XENON)	3000FT.	KRX-140	TSS
TSS-6000	TSS	TSS	TSS-74K (ARC CARBON)	6000FT. (A) (FILM RE-WIND SYSTEM)	TSS-85A	TSS
TSS-6000	TSS	TSS	TXH (2K XENON)	6000FT. (A) (FILM RE-WIND SYSTEM)	KRX-80	TSS
TSS-6000	TSS	TSS	TXH (3K XENON)	6000FT. (A) (FILM RE-WIND SYSTEM)	KRX-100	TSS
TSS-6000	TSS	TSS	TXH (4K XENON)	6000FT. (A) (FILM RE-WIND SYSTEM)	KRX-140	TSS
TSS-6000	TSS	TSS	TSS-74K (ARC CARBON)	6000FT. (B)	TSS-85A	TSS
TSS-6000	TSS	TSS	TXH (2K XENON)	6000FT. (B)	KRX-80	TSS
TSS-6000	TSS	TSS	TXH (3K XENON)	6000FT. (B)	KRX-100	TSS
TSS-6000	TSS	TSS	TXH (4K XENON)	6000FT. (B)	KRX-140	TSS

Tokiwa PROJECTORS & PARTS




T-54 35mm PORTABLE SOUND PROJECTOR



T60-HALOGEN 35mm PORTABLE SOUND PROJECTOR



T-60X 35mm PROJECTOR WITH XENON LAMPHOUSE



TSS-X 35mm SOUND PROJECTOR WITH XENON LAMPHOUSE




T-60 35mm PORTABLE SOUND PROJECTOR




T60-1000X 35mm SOUND PROJECTOR




TP-HALOGEN
35mm SOUND PROJECTOR




TSR-12000 35mm SOUND PROJECTOR




T60-500X 35mm PORTABLE SOUND PROJECTOR



T6000-HALOGEN 35mm SOUND PROJECTOR (6000 ft.)



TSR-6000A 35mm SOUND PROJECTOR 16000 ft.1



TSR-6000-B 16/35mm SOUND PROJECTOR



TOKIWA CO., LTD. Tokyo, Japan

